



SHERWOOD

MACHINERY PTY. LTD. A.B.N. 14 003 931 557

263 FERNDAL RD., (P.O. BOX 6)

BUNDANOON N.S.W. 2578

Phone: 02-4883 6093

Fax: 02-4883 6576

Email: sherwoodsales@bigpond.com

Web Site: www.sherwoodmachinery.com.au

SLASHERS

(Adjustable skids, front and rear guarding standard on all models)

					kg
M112406	CENTRAL	1.2m (4')	60 HP	HEAVY DUTY	275
M116406	OFF SET	1.2m (4')	60 HP	HEAVY DUTY	275
M112456	CENTRAL	1.35m (4'6")	60 HP	HEAVY DUTY	300
M116456	OFF SET	1.35m (4'6")	60 HP	HEAVY DUTY	300
M112506	CENTRAL	1.5m (5')	60 HP	HEAVY DUTY	350
M116506	OFF SET	1.5m (5')	60 HP	HEAVY DUTY	350
M112508	CENTRAL	1.5m (5')	80 HP	HEAVY DUTY	405
M116508	OFF SET	1.5m (5')	80 HP	HEAVY DUTY	405
M112608	CENTRAL	1.8m (6')	80 HP	HEAVY DUTY	550
M116608	OFF SET	1.8m (6')	80 HP	HEAVY DUTY	550
M112612	CENTRAL	1.8m (6')	120 HP	EXTRA HEAVY DUTY	580
M116612	OFF SET	1.8m (6')	120 HP	EXTRA HEAVY DUTY	580
M112712	CENTRAL	2.1m (7')	120 HP	EXTRA HEAVY DUTY	675
M113002	WHEEL KIT - HEAVY DUTY SOLID RUBBER				56

DOUBLE CUT SLASHERS

M11208T130	CENTRAL	2.4m (8')	130 HP	EXTRA HEAVY DUTY	880
------------	---------	-----------	--------	------------------	-----

TRIPLE CUT SLASHERS

M11210T130	CENTRAL	3.0m (10')	130 HP	EXTRA HEAVY DUTY	1220
M11212T130	CENTRAL	3.6m (12')	130 HP	EXTRA HEAVY DUTY	1400



SHERWOOD

MACHINERY PTY. LTD. A.B.N. 14 003 931 557

263 FERNDALE RD., (P.O. BOX 6)
BUNDANOON N.S.W. 2578

Phone: 02-4883 6093

Fax: 02-4883 6576

Email: sherwoodsales@bigpond.com

Web Site: www.sherwoodmachinery.com.au



1 METRE



5FT 60HP

ALL SLASHERS COME COMPLETE WITH FRONT AND REAR GUARDING



6FT 80HP



4FT 60HP

SLASHERS



WHEEL KIT



6FT 120HP

ALL SLASHERS COME COMPLETE WITH FRONT AND REAR GUARDING



SHERWOOD MACHINERY PTY. LTD.

A.B.N. 14 003 931 557

**FERNDALE RD., (P.O. BOX 6) BUNDANOON N.S.W. 2578
Australia Phone: 02-4883 6093 Fax: 02-4883 6576**

Sherwood Machinery Pty Ltd offers a comprehensive range of heavy duty slashers in centrally mounted or off-set configurations, with 60 to 120 hp gearboxes, in sizes 1 metre to 2.1 metres, all with adjustable skids, RHS headstocks, slip clutches, and drive shafts included, solidly constructed, built to last and finished in rust-fighter undercoat covered with high quality enamel paints.

Important features on all heavy duty Sherwood slashers include: front and rear guarding, sweep down front and rear body for downdraft and deflection safety; un-cluttered top deck for easy washdown; re-enforcing bars partly open at connection joints (to avoid water and material being trapped on the other-wise smooth deck, thus ensuring longer rust-free life); strong rectangular hollow section (RHS) headstocks with top linkage pivot instead of easily bendable flat section materials, and the three position adjustable skids, using fixed holes (rather than slots), thus preventing any unwanted height movement during slashing procedures. For quality you will enjoy - Sherwood slashers.

SLASHER OPTIONS		
M11302	WHEEL KIT - HEAVY DUTY SEGMENTED RUBBER	

SLASHERS

CONFIGURATION	7' 120HP CENTRAL	
MODEL	M112712	
HEAD STOCK LOCATION	CENTRAL	
GEARBOX	120 HP (90kW)	
CUTTING WIDTH	2.1 m (7')	
CUTTING HEIGHT	ADJUSTABLE	
BLADE SIZE	490 X 75 X 10 mm	
BLADE TIP SPEED AT 540 RPM	115 m/sec	
NO. OF BLADES	2	
DRIVE SHAFT LENGTH (MAX/MIN)	100 / 165 cm	
THICKNESS OF BODY STEEL	6 mm	
LINKAGE CATEGORY	DUAL CAT 1 / 2	
CLUTCH TYPE	8" SLIP CLUTCH	
HEIGHT ADJUSTMENT	3 POSITIVE HOLES	
POWER REQUIRED	UP TO 120 HP(90kW)	
WEIGHT (kg)	675	
CONFIGURATION	6' 120HP CENTRAL	6' 120HP O/SET
MODEL	M112612	M116612
HEAD STOCK LOCATION	CENTRAL	OFF-SET
GEARBOX	120 HP (90kW)	120 HP (90kW)
CUTTING WIDTH	1.8 m (6')	1.8 m (6')
CUTTING HEIGHT	ADJUSTABLE	ADJUSTABLE
BLADE SIZE	490 X 75 X 10 mm	490 X 75 X 10 mm
BLADE TIP SPEED AT 540 RPM	100 m/sec	100 m/sec
NO. OF BLADES	2	2
DRIVE SHAFT LENGTH (MAX/MIN)	100 / 165 cm	100 / 165 cm
THICKNESS OF BODY STEEL	6 mm	6 mm
LINKAGE CATEGORY	DUAL CAT 1 / 2	DUAL CAT 1 / 2
CLUTCH TYPE	8" SLIP CLUTCH	8" SLIP CLUTCH
HEIGHT ADJUSTMENT	3 POSITIVE HOLES	3 POSITIVE HOLES
POWER REQUIRED	UP TO 120 HP(90kW)	UP TO 120 HP(90kW)
WEIGHT (kg)	580	580

CONFIGURATION	6' 80HP CENTRAL	6' 80HP O/SET
MODEL	M112608	M116608
HEAD STOCK LOCATION	CENTRAL	OFF-SET
GEARBOX	80 HP (60kW)	80 HP (60kW)
CUTTING WIDTH	1.8 m (6')	1.8 m (6')
CUTTING HEIGHT	ADJUSTABLE	ADJUSTABLE
BLADE SIZE	490 X 75 X 10 mm	490 X 75 X 10 mm
BLADE TIP SPEED AT 540 RPM	100 m/sec	100 m/sec
NO. OF BLADES	2	2
DRIVE SHAFT LENGTH (MAX/MIN)	100 / 165 cm	100 / 165 cm
THICKNESS OF BODY STEEL	6 mm	6 mm
LINKAGE CATEGORY	DUAL CAT 1 / 2	DUAL CAT 1 / 2
CLUTCH TYPE	8" SLIP CLUTCH	8" SLIP CLUTCH
HEIGHT ADJUSTMENT	3 POSITIVE HOLES	3 POSITIVE HOLES
POWER REQUIRED	UP TO 80 HP(60kW)	UP TO 80 HP(60kW)
WEIGHT (kg)	550	550

CONFIGURATION	5' 80HP CENTRAL	5' 80HP O/SET
MODEL	M112508	M116508
HEAD STOCK LOCATION	CENTRAL	OFF-SET
GEARBOX	80 HP (60kW)	80 HP (60kW)
CUTTING WIDTH	1.5 m (5')	1.5 m (5')
CUTTING HEIGHT	ADJUSTABLE	ADJUSTABLE
BLADE SIZE	490 X 75 X 10 mm	490 X 75 X 10 mm
BLADE TIP SPEED AT 540 RPM	83 m/sec	83 m/sec
NO. OF BLADES	2	2
DRIVE SHAFT LENGTH (MAX/MIN)	100 / 165 cm	100 / 165 cm
THICKNESS OF BODY STEEL	5 mm	5 mm
LINKAGE CATEGORY	DUAL CAT 1 / 2	DUAL CAT 1 / 2
CLUTCH TYPE	8" SLIP CLUTCH	8" SLIP CLUTCH
HEIGHT ADJUSTMENT	3 POSITIVE HOLES	3 POSITIVE HOLES
POWER REQUIRED	UP TO 80 HP(60kW)	UP TO 80 HP(60kW)
WEIGHT (kg)	405	405

CONFIGURATION	5' 60HP CENTRAL	5' 60HP O/SET
MODEL	M112506	M116506
HEAD STOCK LOCATION	CENTRAL	OFF-SET
GEARBOX	60 HP (45kW)	60 HP (45kW)
CUTTING WIDTH	1.5 m (5')	1.5 m (5')
CUTTING HEIGHT	ADJUSTABLE	ADJUSTABLE
BLADE SIZE	490 X 75 X 10 mm	490 X 75 X 10 mm
BLADE TIP SPEED AT 540 RPM	83 m/sec	83 m/sec
NO. OF BLADES	2	2
DRIVE SHAFT LENGTH (MAX/MIN)	100 / 165 cm	100 / 165 cm
THICKNESS OF BODY STEEL	5 mm	5 mm
LINKAGE CATEGORY	CAT 1	CAT 1
CLUTCH TYPE	6" SLIP CLUTCH	6" SLIP CLUTCH
HEIGHT ADJUSTMENT	3 POSITIVE HOLES	3 POSITIVE HOLES
POWER REQUIRED	UP TO 60 HP(45kW)	UP TO 60 HP(45kW)
WEIGHT (kg)	350	350

CONFIGURATION	4'6" 60HP CENTRAL	4'6" 60HP O/SET
MODEL	M112456	M116456
HEAD STOCK LOCATION	CENTRAL	OFF-SET
GEARBOX	60 HP (45kW)	60 HP (45kW)
CUTTING WIDTH	1.35 m (4'6")	1.35 m (4'6")
CUTTING HEIGHT	ADJUSTABLE	ADJUSTABLE
BLADE SIZE	490 X 75 X 10 mm	490 X 75 X 10 mm
BLADE TIP SPEED AT 540 RPM	75 m/sec	75 m/sec
NO. OF BLADES	2	2
DRIVE SHAFT LENGTH (MAX/MIN)	75 / 110 cm	75 / 110 cm
THICKNESS OF BODY STEEL	5 mm	5 mm
LINKAGE CATEGORY	CAT 1	CAT 1
CLUTCH TYPE	6" SLIP CLUTCH	6" SLIP CLUTCH
HEIGHT ADJUSTMENT	3 POSITIVE HOLES	3 POSITIVE HOLES
POWER REQUIRED	UP TO 60 HP(45kW)	UP TO 60 HP(45kW)
WEIGHT (kg)	300	300

CONFIGURATION	4' 60HP CENTRAL	4' 60HP O/SET
MODEL	M112406	M116406
HEAD STOCK LOCATION	CENTRAL	OFF-SET
GEARBOX	60 HP (45kW)	60 HP (45kW)
CUTTING WIDTH	1.2 m (4')	1.2 m (4')
CUTTING HEIGHT	ADJUSTABLE	ADJUSTABLE
BLADE SIZE	365 X 75 X 12 mm	365 X 75 X 12 mm
BLADE TIP SPEED AT 540 RPM	67 m/sec	67 m/sec
NO. OF BLADES	2	2
DRIVE SHAFT LENGTH (MAX/MIN)	75 / 110 cm	75 / 110 cm
THICKNESS OF BODY STEEL	5 mm	5 mm
LINKAGE CATEGORY	CAT 1	CAT 1
CLUTCH TYPE	6" SLIP CLUTCH	6" SLIP CLUTCH
HEIGHT ADJUSTMENT	3 POSITIVE HOLES	3 POSITIVE HOLES
POWER REQUIRED	UP TO 60 HP(45kW)	UP TO 60 HP(45kW)
WEIGHT (kg)	275	275

CONFIGURATION		1m 60HP O/SET
MODEL		M116326
HEAD STOCK LOCATION		OFF-SET
GEARBOX		60 HP (45kW)
CUTTING WIDTH		1 metre
CUTTING HEIGHT		ADJUSTABLE
BLADE SIZE		365 X 75 X 12 mm
BLADE TIP SPEED AT 540 RPM		55 m/sec
NO. OF BLADES		2
DRIVE SHAFT LENGTH (MAX/MIN)		75 / 110 cm
THICKNESS OF BODY STEEL		2.5 mm
LINKAGE CATEGORY		CAT 1
CLUTCH TYPE		6" SLIP CLUTCH
HEIGHT ADJUSTMENT		3 POSITIVE HOLES
POWER REQUIRED		UP TO 40 HP(30kW)
WEIGHT (kg)		185

CONFIGURATION	10' 130HP CENTRAL	12' 130HP CENTRAL
MODEL	M112406	M116406
HEAD STOCK LOCATION	CENTRAL	CENTRAL
GEARBOX	130 HP (97kW)	130 HP (97kW)
CUTTING WIDTH	3.0 m (10')	3.6 m (12')
CUTTING HEIGHT	ADJUSTABLE	ADJUSTABLE
BLADE SIZE	365 X 75 X 12 mm	365 X 75 X 12 mm
BLADE TIP SPEED AT 540 RPM	55 m/sec	67 m/sec
NO. OF BLADES	6	6
DRIVE SHAFT LENGTH (MAX/ MIN)	100 / 165 cm	100 / 165 cm
THICKNESS OF BODY STEEL	5 mm	5 mm
LINKAGE CATEGORY	CAT 1/2	CAT 1/2
CLUTCH TYPE	8" SLIP CLUTCH	8" SLIP CLUTCH
HEIGHT ADJUSTMENT	3 POSITIVE HOLES	3 POSITIVE HOLES
POWER REQUIRED	130 HP (97kW)	130 HP (97kW)
WEIGHT (kg)	1220	1400
CONFIGURATION		8' 130HP CENTRAL
MODEL		M11208T130
HEAD STOCK LOCATION		CENTRAL
GEARBOX		130 HP (97 Kw)
CUTTING WIDTH		2.4 metre
CUTTING HEIGHT		ADJUSTABLE
BLADE SIZE		365 X 75 X 12 mm
BLADE TIP SPEED AT 540 RPM		67 m/sec
NO. OF BLADES		4
DRIVE SHAFT LENGTH (MAX/ MIN)		100 / 165 cm
THICKNESS OF BODY STEEL		5 mm
LINKAGE CATEGORY		CAT 1/2
CLUTCH TYPE		8" SLIP CLUTCH
HEIGHT ADJUSTMENT		3 POSITIVE HOLES
POWER REQUIRED		100 HP (75 Kw)
WEIGHT (kg)		880



SHERWOOD

MACHINERY PTY. LTD. A.B.N. 14 003 931 557

263 FERNDALE RD., (P.O. BOX 6)

BUNDANOON N.S.W. 2578

Phone: 02-4883 6093

Fax: 02-4883 6576

Email: sherwoodsales@bigpond.com

Web Site: www.sherwoodmachinery.com.au

TRACTOR/ SLASHER COMPATIBILITY

As a general guide only the following horse power /slasher size can be applied.

TRACTOR	SLASHER SIZE	SLASHER WEIGHT
20 hp	1 Metre	185 kg
30 hp	4ft /4ft 6in	275 / 300 kg
40-50hp	4ft 6in /5ft 60hp	300 / 350 kg
60-70 hp	5ft 80hp / 6ft80hp	405 / 550 kg
80-90 hp	6ft 120hp/ 7ft	580 / 675 kg
100 hp and above	Double or Triple cut models	1200 kg and up

If the slasher being used lifts the front wheels of the tractor off the ground when you raise the 3pl, then the slasher is too big for the tractor.

Weight, horse power and physical size of your tractor. eg older model tend to be larger in size with smaller horse power in relation to more modern compact tractors.

Other considerations include front wheel weights, front end loader attachments. Is the slasher to be shared between neighbours ? If so, does the slasher size suit all tractors it is to be used on?

CONSULT YOUR DEALER FOR TRACTOR / SLASHER COMPATIBILITY TO ENSURE YOU GET THE RIGHT COMBINATION.

REFER TO YOUR TRACTOR MANUAL FOR 3PL LIFTING CAPACITIES



SHERWOOD

MACHINERY PTY. LTD. A.B.N. 14 003 931 557

263 FERNDALE RD., (P.O. BOX 6)

BUNDANOON N.S.W. 2578

Phone: 02-4883 6093

Fax: 02-4883 6576

Email: sherwoodsales@bigpond.com

Web Site: www.sherwoodmachinery.com.au

8 FT DOUBLE CUT 10 & 12 FT TRIPLE CUT SLASHERS



DOUBLE CUT MODEL SHOWN

SHERWOOD HEAVY DUTY DOUBLE & TRIPLE CUT SLASHERS TO SUIT TRACTORS FROM 100HP

TWIN WHEEL KITS ARE STANDARD

COMPLETE WITH ALL GUARDING, ADJUSTABLE SKIDS, RHS HEADSTOCK WITH TOP LINKAGE PIVOT, CLUTCH AND DRIVE SHAFT.

M11208T130	8FT DOUBLE CUT – CENTRAL MOUNT 130HP GEARBOXES
M11210T130	10FT TRIPLE CUT -- CENTRAL MOUNT 130HP GEARBOXES
M11212T130	12FT TRIPLE CUT – CENTRAL MOUNT 130HP GEARBOXES